



Customer:	Customer Contact:	Freight:
Reference:	Company:
Order No.:	Tel.	Delivery Address:
Order date:	Fax:	<input type="checkbox"/> Usual
Delivery date required:	E-mail:	Other:

CONTROLLER
NºStops: (Max. Stops 8)

System Drive

- Direct Start Hydraulic
 Star Delta Hydraulic
 Traction VVVF

Supply Voltage 50/60Hz.

- 230V Single-phase
 230V Three-phase
 400V

Others:

Motor
Motor Power (HP): (kW).....

Rated Current (A):

Motor Protection

- Thermal Relay
 PTC in motor (Thermistor)

Valves Model

- 1 Valve for down
 Válvula a 48V VDC VAc

Other:

Documentation

- Spanish
 English
 French
 Portuguese
 Other:

Delivery Country:

.....

PREWIRING
Distance

From cabinet to motor m (4m standard)

From cabinet to shaft m (7m standard)

Distance
Entrances Between floors

- | A | B (4m standard) | Controller Location |
|-----------------------------|--------------------------------|--|
| <input type="checkbox"/> F7 | <input type="checkbox"/> | <input type="checkbox"/> Highest Floor |
| <input type="checkbox"/> F6 | <input type="checkbox"/> | <input type="checkbox"/> Lowest Floor |
| <input type="checkbox"/> F5 | <input type="checkbox"/> | |
| <input type="checkbox"/> F4 | <input type="checkbox"/> | |
| <input type="checkbox"/> F3 | <input type="checkbox"/> | |
| <input type="checkbox"/> F2 | <input type="checkbox"/> | |
| <input type="checkbox"/> F1 | <input type="checkbox"/> | |
| <input type="checkbox"/> F0 | <input type="checkbox"/> | |

Car doors

- Manual
 Automatic
 Single-Phase Three-Phase

CONTROLLER OPTIONS

- Electrical locks 24VDC
 Car stopped at floor indication
 Landing doors with pre-lock contact
 Yes No
 Leveling hydraulic System

Motor

Voltage (V):

Power (HP):

Rated Current (A):

Valves Voltage

 (V): VDC VAc

PREWIRING OPTIONS

- Double Piston
 Positioning Indicator
 Arrival Gong
 Shaft Lighting
 Socket in the Pit

Socket Type

- Schuko UK France
 Swiss Others:

SEND FORM BY E-MAIL

 Before submitting the save the file
Renaming.

Send
COMMENTS:

.....

.....

.....

.....

.....