

Customer:	Customer Contact:	Freight:
Reference:	Company:
Order No. :	Tel.:	Delivery Address:
Order date:	Fax:	<input type="checkbox"/> Usual
Delivery date required:	E-mail:	Other:

CONTROLLER

Controller Type
 HIDRA

Number of Cabins
 1 Cabin (Simplex)
 2 Cabin (Duplex)
 3 Cabin (3-cabin group)
 4 Cabin (4-cabin group)

Collection
 Non-Collective (Simplex only)
 Up Collective
 Down Collective
 Full Collective

Floors No.
 Cabin 1..... Cabin 2.....
 Cabin 3..... Cabin 4.....

Floor Symbols

Lowest Floor Upper Floor

Access Floor

Floor Symbols per Cabin

Cabin 1
 Cabin 2
 Cabin 3
 Cabin 4

Position Indicators

Display in Cabin:.....

Fixing System:.....

Display at Landings:.....

Fixing System:.....

In Floors:.....

With Machine Room

Traction 1-Speed 2-Speed
Hydraulic Direct Start Star-Delta

Traction with VVVF
 Synchronous Motor Asynchronous Motor

Without Machine Room

VVVF Synchronous Motor
 MRL (All in landing cabinet)
 MRL-F (Control in door frame and power at shaft)
 MRL-S (Control at landing and power at shaft)

VVVF CONTROLLER OPTIONS

Rescue Type
 Unbalancing Automatic
 Energizing the Motor Manual

Model VVVF
 Fuji Control Techniques

Provide keypad
 Yes NO

ENGINE INFORMATION

Supply Voltage 50/60Hz.

230V Three-phase 400V Three-phase
 230V Single-phase Others:

Neutral: Yes No

Motor
Power (HP): **(kW):**

Rated Current (A):

Motor Encoder:
Tipo: **Model:**

Manufacturer:

Speed cabin: m/s

Brake
Overvoltage: (V) Dc Ac
Maintenance: (V)

Valves Model (Hydraulic)
 GMV 3010 GMV 3100 GMV NGV
 BLAIN EV1 BLAIN EV10 BLAIN EV100
 BUCHER LRV MORIS

Other:

Valves Voltage: (V) Dc Ac

CONTROLLER OPTIONS

Doors Model
 Retiring Ramp
 Voltage: (V) Dc Ac
 Single-phase Three-phase
 VVVF Doors Emergency
 Yes No

Other:

Brand: **Model:**

Voltage: (V) Dc Ac
 Double car entrance
 Alternated Simultaneous Selective

Entrance Floors
 A
 B

Speed governor with remote test
 Number of coils:

Voltage: (V) Dc Ac
 (190Vdc standard)

INFORMATION AND CONTROL SIGNALS

Signals at Landing
 Pre-direction Arrows (hall lanterns)
 Evacuation call

Signals at Cabin
 Pre-direction Arrows
 VIP (cabin control)
 Full load
 Overload
 Photocell
 Door close pushbutton
 Arrival Gong
 Temporized cabin light

REGULATIONS

EN 81-70 EN 81-72 EN 81-73
 EN 81-21 Short pit Short head
 Device A3 Type:

DOCUMENTATION

Spanish English French
 Portuguese Other:

COMMENTS:

.....

.....

.....

.....

Customer:	Customer Contact:	Freight:
Reference:	Company:
Order No. :	Tel.	Delivery Address:
Order date:	Fax:	<input type="checkbox"/> Usual
Delivery date required:	E-mail:	Other:

WIRING LENGHTS

From cabinet to motor :m (**5** m standar)

Controller to Shaft :m (**9** m standar)

Head :m Short Head (1)

Pit :m Short Pit (1)

Toe Guard

Control Panel Location

Highest Floor Lowest Floor Other:

Pulleys Room Yes No

Shaft Lihgting Bulbs Fluorescent

Overspeed Location Machine Room Shaft

Cabin

FLOORS DISTANCES
(**3,5** m standar)

F9m	F18m
F8m	F17m
F7m	F16m
F6m	F15m
F5m	F14m
F4m	F13m
F3m	F12m
F2m	F11m
F1m	F10m
F0m	F9m

(1) Indicate measurements for Short Head and Short Pit.

LANDING OPTIONS

Signals

Open door Busy

Directional Arrows Pre-Directional Arrows Emergency Arrows

FLD Arrow Modules

Red Blue Bolt attachment Clip attachment

Car Presence Lighting Door Contacts PLR Modules

Position Indicators

Ground Floor All Floors

Push Buttons

One per Car Shared One Firefighters Key at P0

CS Supplies Customer Supplies Wiring Operation

Doors

Semi automatic At Stop

Automatic At Stop

EN 81-70

Gongs + Arrows Placement In Car Landing

CAR OPTIONS

Light Warning Signs

Push Button Arrows Door Top Arrows

Intercom

SAR Inspection Box SAR in COP

Customer Intercom Intercom

Induction Loop

Car Top COP

Synthetizer Language

Castellano Catalán Euskera English Français

Portugués Deutch Italiano Norwegian

Other Options

Inspection Box Lighting

Plug Type: Schuco UK Swiss

Emergency Lighting : CS Supply LCD function

Weight Device

Cable N° of Cables : Ud. Diameter of Cables : mm

In Platform N° of Cells : Ud. N° de Dummies : Ud.

Tension : 24Vdc 230Vac

Supply? : Yes No

Push Button Options

Short COP Full Height COP

CS Supply Customer Supply Wiring Operation

COMMENTS:

.....


.....

.....

.....

SEND FORM BY E-MAIL

Before submitting the save the file Renaming.


Send